

# **Economic and Social Council**

Distr.: General 20 December 2016

Original: English

### **Economic Commission for Europe**

**Inland Transport Committee** 

#### **World Forum for Harmonization of Vehicle Regulations**

171st session

Geneva, 14-17 March 2017 Item 4.9.21 of the provisional agenda 1958 Agreement: Consideration of draft amendments to existing Regulations submitted by GRE

# Proposal for the 02 series of amendments to Regulation No. 113 (Headlamps emitting a symmetrical passing-beam)

### Submitted by the Working Party on Lighting and Light-Signalling\*

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its seventy-sixth session (ECE/TRANS/WP.29/GRE/76, paras. 10 and 15). Τt is ECE/TRANS/WP.29/2013/93, based on ECE/TRANS/WP.29/GRE/2013/55/Rev.1, ECE/TRANS/WP.29/GRE/2014/3, ECE/TRANS/WP.29/GRE/2016/14 and Annex IV to ECE/TRANS/WP.29/GRE/75 and ECE/TRANS/WP.29/GRE/2016/32. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee AC.1 for consideration at their March 2017 sessions.

<sup>\*</sup> In accordance with the programme of work of the Inland Transport Committee for 2016–2017 (ECE/TRANS/254, para. 159 and ECE/TRANS/2016/28/Add.1, cluster 3.1), the World Forum will develop, harmonize and update Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

# Proposal for the 02 series of amendments to Regulation No. 113 (Headlamps emitting a symmetrical passing-beam)

Paragraph 1.3.1., amend to read:

- "1.3.1. The trade name or mark:
  - (a) Lamps bearing the same trade name or mark but produced by different manufacturers shall be considered as being of different types;
  - (b) Lamps produced by the same manufacturer differing only by the trade name or mark shall be considered as being of the same type."

Insert a new paragraph 2.4., to read;

- "2.4. In the case of a type of lamp differing only by the trade name or mark from a type that has already been approved it shall be sufficient to submit:
- 2.4.1. A declaration by the lamp manufacturer that the type submitted is identical (except in the trade name or mark) with and has been produced by the same manufacturer as, the type already approved, the latter being identified by its approval code;
- 2.4.2. Two samples bearing the new trade name or mark or equivalent documentation."

Paragraph 5., amend to read:

## "5. General specifications

The requirements contained in sections 5. "General specifications" and 6. "Individual specifications" and in the Annexes referenced in the said sections of Regulations Nos. 53, 74 or 86, and their series of amendments in force at the time of application for the lamp type approval shall apply to this Regulation.

The requirements pertinent to each lamp and to the category/ies of vehicle on which the lamp is intended to be installed shall be applied, where its verification at the moment of lamp type approval is feasible.

5.1. ..."

Paragraph 9.1., amend to read:

"9.1. Headlamps shall be so manufactured as to conform to the type approved under this Regulation.

The compliance with the requirements set forth in paragraphs 6. and 7. above shall be verified as follows:"

Paragraph 9.2. (former), renumber as paragraph 9.1.1.

Paragraph 9.3. (former), renumber as paragraph 9.1.2.

Paragraph 9.4. (former), renumber as paragraph 9.2.

Paragraph 9.5. (former), renumber as paragraph 9.3.

Paragraph 9.6. (former), renumber as paragraph 9.4.

#### Insert the following paragraphs

13.5. As from the official date of entry into force of the 02 series of amendments, no Contracting Party applying this Regulation shall refuse to grant approval under this Regulation as amended by the 02 series of amendments.

13.6. As from 01 September 2019 Contracting Parties applying this Regulation shall grant approvals only if the type of direction indicator to be approved meets the requirements of this Regulation as amended by the 02 series of amendments.

#### Renumber existing paragraph 13.5 into 13.7

Annex 4,

Paragraph 1.2.1.1.2., amend to read:

"1.2.1.1.2. For headlamp with the outside lens in plastic material:

The mixture of water and polluting agent to be applied to the headlamp shall be composed of:

- (a) 9 parts by weight of silica sand with a particle size of 0-100 μm,
- (b) 1 part by weight of vegetal carbon dust produced from beech wood with a particle size of  $0-100 \mu m$ ,
- (c) 0.2 part by weight of NaCMC<sup>3</sup>,
- (d) 5 parts by weight of sodium chloride (pure at 99 per cent),
- (e) 13 parts by weight of distilled water with a conductivity of  $\leq 1$  mS/m,
- (f)  $2 \pm 1$  drops of surfactant.<sup>4</sup>

The mixture shall not be more than 14 days old."

#### Paragraph 2.2., amend to read:

- "2.2. Test results
- 2.2.1. The result in milliradians (mrad) shall be considered as acceptable for a headlamp producing a passing beam, only when the absolute value  $\Delta$   $r_I = \mid r_3 r_{60} \mid$  recorded on the headlamp is not more than 1.0 mrad ( $\Delta$   $r_I < 1.0$  mrad) upwards and not more than 2.0 mrad ( $\Delta$   $r_I \leq 2.0$  mrad) downwards.
- 2.2.2. However, if this value is:

Movement	
Upward	more than 1.0 mrad but not more than 1.5 mrad $(1.0 \text{ mrad} \leq \Delta \text{ r}_I \leq 1.5 \text{ mrad})$
Downward	more than 2.0 mrad but not more than 3.0 mrad $(2.0 \text{ mrad} \leq \Delta \text{ r}_{I} \leq 3.0 \text{ mrad})$

a further sample of a headlamp mounted on a test fixture representative of the correct installation on the vehicle shall be tested as described in paragraph 2.1. after being subjected three consecutive times to the cycle as described below, in order to stabilize the position of mechanical parts of the headlamp:

(a) Operation of the passing beam for one hour (the voltage shall be adjusted as specified in paragraph 1.1.1.2.);

(b) One hour period with the lamp switched off.

After these three cycles, the headlamp type shall be considered as acceptable if the absolute values  $\Delta r$  measured according to paragraph 2.1. above on this further sample meet the requirements in paragraph 2.2.1. above."

#### Annex 5,

#### Paragraph 1.4., amend to read:

"1.4. With respect to the verification of the change in vertical position of the "cutoff" line under the influence of heat, the following procedure shall be applied
(Classes B, C, D and E headlamps only):

One of the sampled headlamps shall be tested according to the procedure described in paragraph 2.1. of Annex 4 after being subjected three consecutive times to the cycle described in paragraph 2.2.2. of Annex 4.

The headlamp shall be considered as acceptable if  $\Delta r$  does not exceed 1.5 mrad upwards and does not exceed 2.5 mrad downwards.

If this value exceeds 1.5 mrad but is not more than 2.0 mrad upwards or exceeds 2.5 mrad but is not more than 3.0 mrad downwards, a second sample shall be subjected to the test after which the mean of the absolute values recorded on both samples shall not exceed 1.5 mrad upwards and shall not exceed 2.5 mrad downwards."

#### Annex 7,

#### Paragraphs 2. to 5., amend to read:

"2. First sampling

In the first sampling four headlamps are selected at random. The first sample of two is marked A, the second sample of two is marked B.

2.1. The conformity of mass-produced headlamps shall not be contested if the deviation of any specimen of samples A and B (all four lamps) is not more than 20 per cent.

In the case, that the deviation of both lamps of sample A is not more than 0 per cent, the measurement can be closed.

2.2. The conformity of mass-produced headlamps shall be contested if the deviation of at least one specimen of samples A or B is more than 20 per cent.

The manufacturer shall be requested to bring his production in line with the requirements (alignment) and a repeated sampling according to paragraph 3. below shall be carried out within two months' time after the notification. The samples A and B shall be retained by the Technical Service until the entire Conformity of Production process is finished.

3. First repeated sampling

A sample of four lamps is selected at random from stock manufactured after alignment.

The first sample of two is marked C, the second sample of two is marked D.

3.1. The conformity of mass-produced headlamps shall not be contested if the deviation of any specimen of samples C and D (all four lamps) is not more than 20 per cent.

In the case, that the deviation of both lamps of sample C is not more than 0 per cent, the measurement can be closed.

- 3.2. The conformity of mass-produced headlamps shall be contested if the deviation of at least:
- 3.2.1. One specimen of samples C or D is more than 20 per cent but the deviation of all specimen of these samples is not more than 30 per cent.

The manufacturer shall again be requested to bring his production in line with the requirements (alignment).

A second repeated sampling according to paragraph 4. below shall be carried out within two months' time after the notification. The samples C and D shall be retained by the Technical Service until the entire Conformity of Production process is finished.

3.2.2. One specimen of samples C and D is more than 30 per cent.

In this case the approval shall be withdrawn and paragraph 5. below shall be applied.

4. Second repeated sampling

A sample of four lamps is selected at random from stock manufactured after alignment.

The first sample of two is marked E, the second sample of two is marked F.

4.1. The conformity of mass-produced headlamps shall not be contested if the deviation of any specimen of samples E and F (all four lamps) is not more than 20 per cent.

In the case, that the deviation of both lamps of sample E is not more than 0 per cent, the measurement can be closed.

4.2. The conformity of mass-produced headlamps shall be contested if the deviation of at least one specimen of samples E or F is more than 20 per cent.

In this case the approval shall be withdrawn and paragraph 5. below shall be applied.

5. Approval withdrawn

Approval shall be withdrawn according to paragraph 10. of this Regulation."

Figure 1, shall be deleted.

5