

4.10 Segment Group 11 - (DSI-STs-DTM-ARR-Gr12): STS - Status

4.10.1 Purpose

This segment is used to transmit a segment relevant to the data set e.g. compilation status, confidentiality status.

4.10.2 Segment Rules

The segment can occur four times, once for each of data privacy, data compilation, quality of data, and data contents. This segment must be present if the Revision Number data element is used in the DSI segment, because it defines the status of the revised data (e.g. completely replaces the original, additional to the original).

4.10.3 Relationships

None.

4.10.4 Segment Format

<i>Tag</i>	<i>Name</i>	<i>M/C</i>	<i>Format</i>	<i>Usage</i>	<i>Imposed Value</i>
C601	STATUS DETAIL	C		R	
9015	Status type, coded	M	an..3	R	
1131	Code list qualifier	C	an..3	X	
3055	Code list responsible agency, coded	C	an..3	D	142
C555	STATUS EVENT	C		R	
9011	Status event, coded	M	an..3	R	
1131	Code list qualifier	C	an..3	X	
3055	Code list responsible agency, coded	C	an..3	D	142
C556	STATUS REASON	C		X	
9013	Status reason, coded	M	an..3		
1131	Code list qualifier	C	an..3		
3055	Code list responsible agency, coded	C	an..3		
9012	Status reason	C	an..35		

4.10.5 Data Element Rules

C601 - Status Detail

9015 - Status type, coded

This identifies one of the three allowed types of the status. It is possible for a private code list to be used by specifying the maintenance agency in data element 3055.

If the value of 142 (Eurostat) is specified for 3055 then the codes used for data elements 9015 **AND** 9011 are to be taken from the code lists specified below.

Code Values:

- 1 data privacy
- 2 data elaboration
- 3 data contents
- 4 quality of data

It is recommended that « privacy » values indicate if data is confidential, i.e. not to be disseminated to other Member States, or not. « Elaboration » values may be used to verify the contents of the data. « Data contents » is used to indicate the meaning of the data set that is transmitted, i.e. it deletes, adds and replaces values, or replaces completely the data set sent previously with the same identifier; or it is a new data set (depending on the value of 9011).

The exact significance of the codes should be agreed between partners.

1131 - Code list qualifier

Not used.

3055 - Code list responsible agency, coded

The value should be 142 (Eurostat).

C555 - Status Event

9011 - Status event, coded

This specifies the status in a coded form. It is possible for a private code list to be used by specifying the maintenance agency in data element 3055.

If the value of 142 (Eurostat) is specified as the maintenance agency for the code in 9015 then the code used for data element 9011 is to be taken from the code list specified below.

Code Values:

- | | |
|------------------------|-------------------|
| <u>PRIVACY</u> : | 1 restricted |
| | 2 unrestricted |
| <u>ELABORATION</u> : | 3 provisional |
| | 4 revised |
| | 5 final |
| <u>DATA CONTENTS</u> : | 6 delete |
| | 7 add and replace |
| | 8 replace |
| | 9 new |

Please refer to the explanation given for 9015. The exact significance of the codes should be agreed between partners.

1131 - Code list qualifier

Not used.

3055 - Code list responsible agency, coded

The value should be 142 (Eurostat).

4.10.6 Examples

(New data set)
STS+3::142+9::142'
(Add restricted data to the data set)
STS+3::142+7::142'
STS+1::142+1::142'